




POONAM INDUSTRIES

A/1-14, VATVA GIDC, VATVA POST OFFICE ROAD, PHASE - 2, AHMEDABAD - 382445
Tel. : 22746493, Email : poonam@poonamvalves.com
Manufacturer of Industrial and agricultural Butterfly Valves

THREE PIECE FLANGE END



Valve Size	Flange OD	Face-to-Face (L)	Flange centre to handle top (H)	Flange Thickness (T)	Internal Diameter
32mm (1")	118	154	100	17	25
50mm (1.5")	140	182	115	20	40
63mm (2")	152	211	125	22	50
75mm (2.5")	166	237	144	25	65
90mm (3")	184	246	165	25	80
110mm (4")	217	300	174	28	100
160mm (6")	278	426	237	38	150

+/- 2mm

Special Features of Three Piece Flange End (Black)

1. Available in Flange Type in 15 mm to 150 mm and in Screw Type in 15 mm to 100 mm.
2. Manufactured from Poly Propylene, a Chemically inert thermoplastic.
3. Can be used upto 90°C Temp.
4. Hydraulically and Pneumatically tested for 15 Kg upto 4".
5. Protective and Resistive from most of the corrosive Chemicals.
6. Flange drilled as per customer's specification.
7. Exelent U.V. stabilty due to presence of carbon black.
8. Heavy duty valve can last for years after installation.

Technical Data

Construction	Multi Piece Body
Design	Three Piece
Size Range	15mm. to 150mm.
Max working temp.	90°C (Consistently)
Gasket/Stem Seal	Neoprene or as specified
Test Pressure	15 kg upto 4"

Bill of Material			
Sr. No.	Part	Qty.	Material
1	Body	1	Polypropylene
2	Ball	1	P.P.
3	Flange End	2	Polypropylene
4	Seat	2	PTFE/HDPE
5	Stem	1	P.P. Reinforced with
6	Bearing	1	Teflon
7	Stud & Nut	5 to 10	M.S. Zinc plated / S.S.
8	Body "O" Ring	2	Neoprene / Teflon
9	Stem "O" Ring	1	Neoprene / Viton
10	Handle	1	P.P. Reinforced with
11	Pin	1	S.S. 304